



Cast Ductile Iron Water Valve Wafer Duo Plate Double Disc Check Valves

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: DEYE
- Certification: ISO9001:2015 PED
- Model Number: DY-CV-Q-12
- Minimum Order Quantity: 10PCS
- Price: USD2-USD20000 each
- Packaging Details: carton box+ ply wooden cases or carton+ Pallets
- Delivery Time: 20 days for usual order, 7 days for stocked items
- Payment Terms: T/T, L/C, D/P
- Supply Ability: 1000pcs one month



Product Specification

- Highlight: Ductile Iron Water Valve, Cast Water Valve, Double disc check valves



More Images



for more products please visit us on piping-industry.com

Product Description

Double Disc Check Valves Model No. CV-Q-12

Ductile iron/cast iron duo plate double disc check valves with DNV GL approved , ANSI 150LBS. Temperature: -40 ~+125

Quick Detail

Double disc spring loaded Check Valve

Design standard	API594 DIN
End connection	Wafer to connect flange ANSI B16.5
Face to face	ANSI DIN F48
Working temperature	-40 ~+125
Test and inspection	API 598
Epoxy powder coated inside and outside Min	250Microns

Product Range:

Body connection Type: wafer, Lug, double flanged

Available Body Material: Cast Iron GG25, Ductile iron GGG40, GGG50, rubber lined body

Available Disc Material: Ductile iron, Bronze, SS304 SS316, Duplex SS2205 SDSS 2507

Optional Seat Ring: EPDM, NBR, PTFE, VITON

Optional Ends: BS4504/EN1092-1 PN16/ ANSI B16.5 RF

Size Range: DN50-DN800 (2"-32")

Pressure Range: PN10, PN16, PN20(150LBS)

Optional surface color: RAL5002, RAL5015. RAL5005, red, black. Or customized

Performance:

- The innovative Dual-Plate Design employs two spring-loaded plates suspended on a central vertical hinge . As Flow Begins, the plates open in response to a resultant force Which acts at the center of the sealed Surface Area
- The Contact point of the reacting spring leg's force acts beyond the center of the plate area, causing the heel to pen first. This prevents rubbing of the seal surface prior to normal plate opening
- As the velocity of flow decreases, torsion spring action reacts automatically. The moves of plates closer to the body seats, reducing the distance and time of travel for closure. By Having
- the plates closer to the body seats at the time of flow reversal. The valve dynamic response is greatly enhanced, This dramatically reduces the water hammer effect
- At closing, the point of spring force causes the plates to close first. This prevents dragging of the heels of the plates and periods maintains seal integrity for much longer Periods

Technical Data Sheets

APPLICATIONS

Steam, Superheated Water, Hot Water, Cold Water, Fluids without acidity or alkalinity properties, Chemicals

DEYE SHIJIAZHUANG DEYE PIPING INDUSTRY CO., LTD Pipefittings Department)



+8613292824811



sales@deyepiping.com



piping-industry.com

No. 368 Youyi St. Shijiazhuang, Hebei, China

